



Drahtseil 637H

Rundlitzenseil 6 x 37 Standard (mit Fasereinlage),
verzinkt, in Kreuzschlag rechts, EN 12385-4

6x37 Standard (1+6+12+18) = 222 Drahte
Seilkategorie Nummer RCN.10 (nach ISO 4309)

- Anschlagseile
- Abspannungen
- Hubwerke
- allgemeine Seiltriebe

Art-Nr.	Seil Ø Konstr.		Gewicht 100m kg	Mindestbruchkraft (MBK) 1770 N/mm ² kN	kp	Preis exkl. MwSt (A) per 100 m
	mm					
011.220.080	8.0	6x37	22.1	33.4	3400	480.00
011.220.090	9.0	6x37	28.0	42.3	4300	515.00
011.220.100	10.0	6x37	34.6	52.2	5310	550.00
011.220.110	11.0	6x37	41.9	63.1	6420	608.00
011.220.120	12.0	6x37	49.8	75.1	7640	702.00
011.220.130	13.0	6x37	58.5	88.2	8970	796.00
011.220.140	14.0	6x37	67.8	102.0	10400	866.00
011.220.150	15.0	6x37	78.0	118.0	12000	971.00
011.220.160	16.0	6x37	88.6	134.0	13600	1076.00
011.220.180	18.0	6x37	112.0	169.0	17200	1217.00
011.220.200	20.0	6x37	138.0	209.0	21200	1404.00
011.220.220	22.0	6x37	167.0	253.0	25700	1638.00
011.220.240	24.0	6x37	199.0	301.0	30600	2024.00
011.220.260	26.0	6x37	234.0	353.0	35900	2387.00
011.220.280	28.0	6x37	271.0	409.0	41600	
011.220.320	32.0	6x37	354.0	534.0	54300	
011.220.360	36.0	6x37	448.0	676.0	68800	
011.220.400	40.0	6x37	554.0	835.0	84900	

