












Tragfähigkeiten Anschlagseile in kg

EN 13414-1



Ømm	1-Strang					2-Strang				3- & 4-Strang	
	direkt	geschnürt	einfach umgelegt			direkt		geschnürt		direkt	
											
Lastfaktor 1	Lastfaktor 0.8	Lastfaktor 2	Lastfaktor 1.4	Lastfaktor 1	Lastfaktor 1.4	Lastfaktor 1	Lastfaktor 1.12	Lastfaktor 0.8	Lastfaktor 2.1	Lastfaktor 1.5	
8	700	560	1400	950	700	950	700	780	560	1450	1050
10	1000	800	2000	1400	1000	1400	1000	1120	800	2100	1500
12	1500	1200	3000	2100	1500	2100	1500	1680	1200	3200	2300
14	2000	1600	4000	2800	2000	2800	2000	2240	1600	4200	3000
16	2700	2150	5400	3800	2700	3800	2700	3020	2150	5700	4050
18	3200	2500	6400	4400	3200	4400	3200	3580	2500	6600	4700
20	4000	3200	8000	5600	4000	5600	4000	4480	3200	8400	6000
22	5000	4000	10000	7000	5000	7000	5000	5600	4000	10500	7500
24	6300	5000	12600	8800	6300	8800	6300	7050	5000	13200	9400
26	7000	5600	14000	9800	7000	9800	7000	7480	5600	14700	10500

* Alle Angaben für Hebebereich (WLL) mit Sicherheitsfaktor 1:5